

Vibrating feeder



ZHENGZHOU YIFAN MACHINERY CO.,LTD.

TEL: +86-371-64628852 +86-371-64963352 FAX: +86-371-64628872
<http://www.yfcrusher.com> <http://www.yfmac.com> E-mail: yfcrusher@yahoo.com.cn



- ◆ **Introduction** : GZG vibrating feeder is mainly rely on the motor to produce vibration force, vibration will be massive, granular materials from storage bin is continuous and uniform feeding prepared by the device.
- ◆ **Features** : GZG vibrating feeder operation convenient, low noise, less consumption, good regulation performance, no flow phenomenon. The vibration motor, to avoid the mechanical vibration to drive and eccentric structure, can avoid the bearing heating and mechanical fatigue problems.

◆Technical Date:

型号	最大给料粒度 mm	激振力 (KN)	振动频率 r/min	双振幅 mm	处理能力 (t/h)		电机功率 (kW)	重量 kg	槽型尺寸 (mm) 宽×长×高	外形尺寸 (mm) 长×宽×高
					水平	-10°				
GZG40-4	100	2×5	1450	4	30	40	2×0.25	171	400×1000×200	1337×750×600
GZG50-4	150	2×5	1450	4	60	85	2×0.25	202	500×1000×200	1374×800×630
GZG63-4	200	2×10	1450	4	110	150	2×0.50	379	630×1250×250	1648×1000×767
GZG70-4	200	2×10	1450	4	120	170	2×0.50	389	700×1290×250	1548×1010×787
GZG80-4	250	2×15	1450	4	160	230	2×0.75	563	800×1500×250	1910×1188×850
GZG90-4	250	2×15	1450	4	180	250	2×0.75	613	900×1483×250	2003×1178×960
GZG100-4	300	2×20	1450	4	270	380	2×1.1	762	1000×1750×250	2190×1362×900
GZG110-4	300	2×20	1450	4	300	420	2×1.5	854	1100×1673×250	2151×1362×970
GZG125-4	350	2×32	1450	4	460	650	2×2.25	1099	1250×2000×315	2540×1500×1030
GZG130-4	350	2×32	1450	4	480	670	2×2.25	1117	1300×2040×300	2544×1556×1084
GZG150-4	500	2×50	1450	3.5	720	1000	2×2.25	1477	1500×2250×300	2794×1776×1220
GZG160-4	500	2×50	1450	4	770	1100	2×2.25	1555	1600×2500×315	3050×1850×1110
GZG180-4	500	2×50	1450	3	900	1200	2×2.25	2350	1800×2325×375	2885×2210×1260
GZG200-4	500	2×50	1450	2.5	1000	1400	2×2.25	2705	2000×3000×400	3490×2400×1220
GZG150-6	500	2×40	960	5	780	1080	2×3	1441	1500×1800×400	2500×1864×1412